



celplast
metallized products



CERAMIS® CPA-001

SILICON OXIDE-COATED NYLON FILM

CPA-001 is an SiO_x-coated nylon film with a combination of excellent clarity and outstanding barrier properties. It is ideally suited for non-retort pouch and lidding applications.

Properties	Typical Value	Units	Test Method
Thickness	60	gauge	
Yield	40,900	in ² /lb	
Tensile Strength	200 MD 200 TD	N/mm ²	ASTM D882
Elongation	130 MD 130 TD	%	ASTM D882
Heat Shrinkage	4.0 MD 4.0 TD	%	130° C, 30 min.
Haze	3.0	%	ASTM D1003-92
Static COF	0.9 SiO _x /SiO _x 0.4 Nylon/Nylon	-	DIN EN ISO 8295
Oxygen Transmission Rate	0.013	cc/100 in ² /d	ASTM D3985-81 @ 23° C, 50%RH CPA-001 / 80 μm CPP

This product is in compliance with the regulation FDA 21 CFR 177.1500. When laminated to an approved substrate, the laminate is compliant with the requirements of EU directive 2002/72/EC.

For more information, visit us at <http://cmp.celplast.com>.

The information and opinions herein are believed to be true and accurate and presented without guarantee or responsibility on our part. No recommendation for use of our product is intended as a patent infringement. No warranty of any kind with respect to patents held by others is implied or intended.

CERAMIS® is a registered trademark of Alcan.

January 2009