



Celplast Metallized Products Limited  
 67 Commander Blvd, Unit 4  
 Toronto, Ontario, M1S 3M7  
 O 416-293-4330 F 416-293-9198  
<http://cmp.celplast.com>

## ZONEMET™ STRIPE METALLIZED POLYESTER FILM

### Typical Values

**Metal One Side, Corona Treat Other Side**

A stripe metallized bi-axially oriented polyester film. Consistently good handling properties, heat stability, slip, and high tensile strength for easy lamination.

Properties	Typical Value	Units	Test Method
Yield	41,600	in <sup>2</sup> /lb	
Standard Gauge	0.48	mil	
Tensile Strength	25,000 MD 30,000 TD	psi	ASTM D882
Tensile Modulus	600,000	psi	ASTM D882
Elongation	90 MD 70 TD	%	ASTM D882
Clear Stripe Limits	.31"		
Met Stripe Limit	.75"		
Coefficient of Friction	Kinetic Static	.45 .55	ASTM D-1894

The polyester side is in compliance with the regulation FDA 21 CFR 177.1630 (f, g, h)  
 The metallized side is FDA approved for indirect food contact.

The information and opinions herein are believed to be true and accurate and presented without guarantee or responsibility on our part. No recommendation for use of our product is intended as a patent infringement. No warranty of any kind with respect to patents held by others is implied or intended.